

Описание на портативные рН-метры. Серия 550, 570

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
Набережные Челны(8552)20-53-41,
Нижний Новгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93



Introducing the new 550 and 570 portable pH meters

Model **550** is a general purpose portable pH meter offering 2 point pH calibration and automatic buffer recognition. This model simultaneously displays both the temperature compensated pH readings and temperature. This small, lightweight meter has an LCD display encompassed in a splash proof housing.

- Simultaneously displays pH and temperature
- Automatic calibration
- Manual or Automatic Temperature Compensation (ATC)
- Auto shut off 10 minutes
- 5000 hours battery life
- 2 year warranty

This meter is supplied ready to use with an epoxy bodied electrode (924 001), a temperature probe (170 101) and buffers and is supplied in a handy carry case.

Model **570** is a general purpose hand held pH, mV and temperature meter. This model offers 2 point calibration and automatic buffer recognition. The unit simultaneously displays either temperature compensated pH readings or electrode potential and temperature. This model has a large easy to read LCD display. The integrated rubber seal ensures that the unit is completely waterproof.

- Simultaneously displays pH or mV and temperature
- Automatic calibration
- Manual or Automatic Temperature Compensation (ATC)
- Auto shut off 10 minutes
- 2500 hours battery life
- Waterproof housing
- 2 year warranty

This meter is supplied ready to use with an epoxy bodied electrode (924 001), a temperature probe (170 100) and buffers and is supplied in a bespoke carry case.

To compliment these new meters Jenway also offers a comprehensive range of application specific electrodes and consumables.

Technical Specification

| | | |
|------------------------------|--------------------|---------------------------------------|
| Model | 550 | 570 |
| Type | pH and temperature | pH, mV and temperature |
| Waterproof | No (IP65) | Yes (IP66/ 67) |
| pH Range | 0 to 14 | - 2 to 16 |
| pH Resolution | 0.01 | 0.01 |
| pH Accuracy | ± 0.05 | ± 0.02 |
| mV Range | N/A | - 1000 to 1000mV |
| mV Resolution | N/A | 1mV |
| mV Accuracy | N/A | ± 1mV |
| ATC | 0 to 60°C | 0 to 100°C |
| Temperature Range | 0 to 100°C | - 39.9 to 149.9°C |
| Temperature Resolution | 0.1 °C | 0.1 °C |
| Temperature Accuracy | ± 0.5°C | ± 0.4°C (- 10 to 70°C) |
| No.of Calibration Points | 2 | 2 |
| Automatic Buffer Recognition | Yes | Yes |
| Auto Shut Off | 10 mins | 10 mins |
| Operating Temperature | 0 to 50°C | 0 to 100°C |
| Battery Life (hours) | 5000 | 2500 |
| pH Connector | BNC | BNC |
| Temperature Connector | 3.5mm jack | Waterproof Lumberg screw-locking type |
| Dimensions (l x w x d) | 128 x 56 x 25mm | 141 x 71 x 32mm |
| Weight | 130g | 230g |

Ordering Information

Meter with Electrode

| Part Code | Description |
|-----------|--|
| 550271 | 550 pH meter supplied in a carry case with epoxy pH electrode (924 001), ATC probe (170 101), buffer sachets and batteries |
| 570271 | 570 pH meter supplied in a carry case with epoxy pH electrode (924 001), ATC probe (170 100), buffer sachets and batteries |

Meter without Electrode

| Part Code | Description |
|-----------|---|
| 550000 | 550 pH meter supplied in a carry case with ATC probe (170 101), buffer sachets and batteries |
| 570000 | 570 pH meter supplied in a carry case with ATC probe (170 100), buffer sachets and batteries |

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
Набережные Челны(8552)20-53-41,
Нижний Новгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93